# Excel Enbeam FTTH Outlet up to 4 Fibres (Unloaded)

Item Code: 200-446









- Hinged splice tray holds up to 4 heatshrink splice protectors
- X Multiple cable entry points
- X Fixing hardware included
- X For use with flangeless adaptors
- X Accepts LC duplex or SC simplex adaptors
- X 2x 40mm splice protectors supplied as standard

#### **Product Overview**

The Excel Enbeam FTTH Surface Mount Box has been designed for applications such as Fibre to the home or Fibre to the Desk.

#### **Product Specifications**

Feature	Values
Surface mounted	yes
With couplers	no
Suitable for number of couplers	2
Suitable for type of fibre	Multi mode/single mode
Width	82.5 mm
Height	105 mm
Depth	25.5 mm

# Excel Enbeam FTTH Outlet up to 4 Fibres (Unloaded)

Item Code: 200-446




### **Additional specifications**


Features	Values
Capacity for 2 port	4 Fibres
Capacity for 4 port	8 Fibres
Material	ABS Plastic
Colour	White
Weight	83 grams
Operating Temprature	-20 to +85 °C


#### **Included accessories**


Accessories	2-port	4-port
Splice Protectors	2	4
Wall fixings	1 set	1 set

#### **Product drawing**









#### **Standards**

Applicable standard	Detail
IEC 61754-1:2013	Fibre optic interconnecting devices and passive components - Fibre optic connector interfaces - Part 1: General and guidance
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements

# Excel Enbeam FTTH Outlet up to 4 Fibres (Unloaded)

excel without compromise.

Item Code: 200-446

EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
UL-94-V-0	Burning stops within 10 seconds after two applications of ten seconds each of a flame to a test bar. NO flaming drips are allowed.
RoHS	Compliant to the Restriction of Hazardous Substances
WFD	Compliant to Waste Framework Directive
SCIP	Compliant - Does Not Contain Substances of Concern in Products

#### **Part Number Table**

Part Number	Description
200-446	Excel Enbeam FTTH Outlet up to 4 Fibres (Unloaded)
200-447	Excel Enbeam FTTH Outlet Loaded with 2x SC/APC OS1/OS2 Simplex Adaptors
200-448	Excel Enbeam FTTH Outlet up to 8 Fibres (Unloaded)
200-449	Excel Enbeam FTTH Outlet Loaded with 4x SC/APC Simplex Adaptors

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

