Item Code: 100-993





X Cat6A solid copper cable
X U/FTP foil screened pairs
X Outer sheath colour black
X External use
X Euroclass Fca
X 25 Year system warranty

Product Overview

Excel Cat6A cable screened U/FTP PE external grade is manufactured to meet and exceed the ISO, CENELEC and TIA standards and supplied on 500m reels. Excel Cat6A screened (U/FTP) cable takes the performance capabilities of copper infrastructure to new levels.

This delivers Class EA/Augmented Category 6 link performance over distances of up 90m which supports the applications including 10GBASE-T, 10 Gigabit Ethernet.

Each cable consists of 4 pairs individually wrapped with high quality, strong, aluminium/polyester foil tape providing screening for each pair.

The foil configuration ensures separation of the pairs that ensures the performance.

The individual pairs are set to different lay lengths to ensure optimum performance.

Product Specifications


Feature	Values
Conductor surface	Bare
AWG size	23
Conductor category	Class 1 = solid
Total number of cores	8
Stranding element	Pairs
Specification core insulation	PE
Core identification	Colour
Overall screening	None

Item Code: 100-993



Outer sheath material Outer sheath colour Black Reaction-to-fire class according to EN 13501-6 Halogen free (acc. EN 60754-1/2) Flame retardant Low smoke (acc. BS EN 61034-2) Outer diameter approx. Installation Temperature Range Outer diameter Range	Conductor screening	Foil
Reaction-to-fire class according to EN 13501-6 Halogen free (acc. EN 60754-1/2) Flame retardant Other Low smoke (acc. BS EN 61034-2) Outer diameter approx. Installation Temperature Range Operating Temperature Range Category Fca Fca Fca Fca Fca Yes Other Other Outer Other Outer Other Outer Other Outer Other Outer Other Other Outer Other Outer Outer	Outer sheath material	PE
Halogen free (acc. EN 60754-1/2) Flame retardant Low smoke (acc. BS EN 61034-2) Outer diameter approx. Installation Temperature Range Operating Temperature Range Category yes 7.2 mm 060 °C -2060 °C 6A (IEC)	Outer sheath colour	Black
Flame retardant Low smoke (acc. BS EN 61034-2) Outer diameter approx. Installation Temperature Range Operating Temperature Range Category Other Other Other Ocher Jest Control Ocher Ocher	Reaction-to-fire class according to EN 13501-6	Fca
Low smoke (acc. BS EN 61034-2) Outer diameter approx. Installation Temperature Range Operating Temperature Range Category yes 7.2 mm 060 °C -2060 °C 6A (IEC)	Halogen free (acc. EN 60754-1/2)	yes
Outer diameter approx. 7.2 mm Installation Temperature Range 060 °C Operating Temperature Range -2060 °C Category 6A (IEC)	Flame retardant	Other
Installation Temperature Range 060 °C Operating Temperature Range -2060 °C Category 6A (IEC)	Low smoke (acc. BS EN 61034-2)	yes
Operating Temperature Range -2060 °C Category 6A (IEC)	Outer diameter approx.	7.2 mm
Category 6A (IEC)	Installation Temperature Range	060 °C
	Operating Temperature Range	-2060 °C
AN (D.)	Category	6A (IEC)
NVP value 75 %	NVP value	75 %

Cross-section diagram



Cable specifications

Features		Values
Dielectric strength		2.5KV DC for 2s
Impedance (Ω)	1-100MHz	100±15
	100-250MHz	100±20
	250-500MHz	100±25
Maximum pulling load		100N
MBR during installation		60mm
MBR installed		50mm

Item Code: 100-993



Standards

Applicable standard	Subject
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
IEC 61156-5:2020	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
EN 50173-2:2018	Information technology. Generic cabling systems - Office premises
BS EN 50288-3-1:2013	Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz
EN 50399:2011+A1:2016	Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 60332-1-2:2004 + A12:2020	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
ANSI/TIA 568-D:2015	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 60754-2:2014	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:2020	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
EN 50575:2014 + A1:2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
IEEE 802.3bt (Type 4)	Compliant to IEEE 802.3bt (Type 4)
RoHS	Compliant to the Restriction of Hazardous Substances
WFD	Compliant to Waste Framework Directive
SCIP	Compliant - Does Not Contain Substances of Concern in Products

Item Code: 100-993



Part Number Table

Part Number	Description
100-990	Excel Solid Cat6A Cable U/FTP LSOH CPR Euroclass Dca 500m Reel Ice Blue
100-990-305M	Excel Solid Cat6A Cable U/FTP LSOH CPR Euroclass Dca 305m Box Ice Blue
100-990-ECA	Excel Solid Cat6A Cable U/FTP LSOH CPR Euroclass Eca 305m Box Ice Blue
100-990-WT-305M	Excel Solid Cat6A Cable U/FTP LSOH CPR Euroclass Dca 305m Box White
100-992	Excel Solid Cat6A Cable U/FTP LSOH CPR Euroclass Dca 500m Reel White
100-993	Excel Solid Cat6A Cable U/FTP PE External Fca 500m Reel Black

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.