

Panel mounted inlet

Part no. 752




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts

Technical specifications

| Ampere | 32 A | | |
|---------------------------|---------------------------------------------------------------|--|--|
| Poles | 7 p | | |
| Voltage | 400 V | | |
| Clock position | 6 h | | |
| Hertz | 50-60 Hz | | |
| Connection technology | Screw terminals | | |
| Contact | nickel plated contacts, highly heat resistant contact carrier | | |
| Protection type | IP 44 | | |
| Weight | 282 g | | |
| Declaration of Conformity | EAC, CQC | | |

Drawing



| Drawing | Amp. | 16 | 32 |
|--------------------------|---------|--------------|-----|
| 2 MB 71 | Poles | 7 | 7 |
| Dim. in mm | a | 85 | 75 |
| | b | 85 | 90 |
| | c | 79 | 90 |
| | d | 64 | 45 |
| | d1 | 10 | 13 |
| | e | 64 | 78 |
| | f | 5.5 | 5.5 |
| | g. | 6 | 6 |
| | g.1 | 2 | 2 |
| | h | 129 | 138 |
| Terminal for cond. cross | | 1 | 2.5 |
| section (mm²) r | ninmax. | — 2.5 | -6 |