

**500.1686**

## PRESA INTERBLOCCATA

16A 3P+T 6h 380-415V 50Hz 60Hz  
136X125MM\_PAR Morsetti a vite Con  
interblocco meccanico



Certificati

| TECHDATA                     |                           | NORME E LEGGI                     |                                                                                                                                                                                                       |
|------------------------------|---------------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Serie commerciale            | Serie OMNIA               | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Tipologia prodotto           | PRESA INTERBLOCCATA       | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica        | PRESA INTERBLOCCATA       |                                   |                                                                                                                                                                                                       |
| Tipo installazione           | PARETE                    |                                   |                                                                                                                                                                                                       |
| Corrente nominale            | 16A                       | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Poli                         | 3P+T                      | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario           | 6h                        |                                   |                                                                                                                                                                                                       |
| Tensione nominale (range)    | 250-400V                  | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock                                                     |
| Tensione nominale            | 380-415V                  |                                   |                                                                                                                                                                                                       |
| Frequenza d'impiego          | 50Hz                      | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Frequenza d'impiego          | 60Hz                      | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colore                       | ROSSO                     |                                   |                                                                                                                                                                                                       |
| Materiale                    | TERMOPLASTICO             |                                   |                                                                                                                                                                                                       |
| Grado di protezione generico | Protetto da getti d'acqua | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock                                                   |
| Grado di protezione IP       | IP44                      |                                   |                                                                                                                                                                                                       |
| Grado di protezione IK       | IK08                      | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Morsetti                     | Morsetti a vite           |                                   |                                                                                                                                                                                                       |
| Materiale di contatto        | CuZn (ottone)             |                                   |                                                                                                                                                                                                       |

|         |                             |
|---------|-----------------------------|
| Flangia | 136X125MM_PAR               |
| Opzioni | Con interblocco meccanico   |
| Note    | SENZA BASE<br>PORTAFUSIBILI |