



**512.1653**

## PRESA DA PARETE

16A 2P+T 6h 200-250V 50Hz 60Hz Morsetti a vite

Certificati

| TECHDATA                     |                           | NORME E LEGGI                     |                                                                                                                                                                                                       |
|------------------------------|---------------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tipologia prodotto           | PRESA DA PARETE           | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Serie commerciale            | Serie OPTIMA              | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica        | PRESA DA PARETE           |                                   |                                                                                                                                                                                                       |
| Tipo installazione           | PARETE                    |                                   |                                                                                                                                                                                                       |
| Corrente nominale            | 16A                       | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Poli                         | 2P+T                      | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario           | 6h                        |                                   |                                                                                                                                                                                                       |
| Tensione nominale (range)    | 200-250V                  | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Tensione nominale            | 200-250V                  |                                   |                                                                                                                                                                                                       |
| Frequenza d'impiego          | 60Hz                      | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Frequenza d'impiego          | 50Hz                      |                                   |                                                                                                                                                                                                       |
| Colore                       | BLU                       | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Materiale                    | TERMOPLASTICO             |                                   |                                                                                                                                                                                                       |
| Grado di protezione generico | Protetto da getti d'acqua |                                   |                                                                                                                                                                                                       |
| Grado di protezione IP       | IP44/IP54                 |                                   |                                                                                                                                                                                                       |
| Grado di protezione IK       | IK08                      |                                   |                                                                                                                                                                                                       |
| Tipo di uscite disponibili   | INCLINATA                 |                                   |                                                                                                                                                                                                       |
| Morsetti                     | Morsetti a vite           |                                   |                                                                                                                                                                                                       |

|                       |               |
|-----------------------|---------------|
| Materiale di contatto | CuZn (ottone) |
| Uscita cavo           | M20X1,5       |