



590.YM67R1

COMANDO FRONTALE LUCCHETTABILE

IP65 standard 67x67mm F1 Y1 D1

EMERGENZA GIALLO/ROSSO TYPE 1, 4, 4X

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie COMMAND	UL 486A	[American Standard] Wire Connectors
Tipologia prodotto	COMANDO FRONTALE LUCCHETTABILE	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch- disconnectors and fuse-combination units
Descrizione sintetica	COMANDO FRONTALE LUCCHETTABILE	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Materiale	TERMOPLASTICO	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Grado di protezione IP	IP65	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch- disconnectors and fuse-combination units
Tipo	EMERGENZA	UL 60947-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 1: General rules
Colore	GIALLO/ROSSO	UL 60947-4-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 4-1: Contactors and Motor-Starters - Electromechanical Contactors and Motor- Starters
Taglia interruttore	F1	CSA C22.2 No. 60947-1-13	[Canadian Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Taglia interruttore	D1	CSA C22.2 No. 60947-4-1-14	[Canadian Standard] Low-voltage switchgear and controlgear - Part 4-1: Contactors and motor-starters - Electromechanical contactors and motor- starters
Taglia interruttore	Y1	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tensione nominale	690V	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch- disconnectors and fuse-combination units
Diametro	standard		
Dimensioni	67x67mm		
Note1	TYPE144X		
Flangia	67X67MM		
		DIRECTIVE LOW	[European Directives] Low Voltage

VOLTAGE 2014/35 Directive
/UE