



**218.32364**

**SPINA MOBILE**

32A 3P+T 3h 380V 50Hz / 440V 60Hz 50Hz  
60Hz Morsetti a vite

Certificati

| TECHDATA                     |                       | NORME E LEGGI                     |                                                                                                                                                                                                       |
|------------------------------|-----------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Serie commerciale            | Serie OPTIMA          | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Tipologia prodotto           | SPINA MOBILE          | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica        | SPINA MOBILE          |                                   |                                                                                                                                                                                                       |
| Tipo installazione           | PORTATILE             |                                   |                                                                                                                                                                                                       |
| Corrente nominale            | 32A                   | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Poli                         | 3P+T                  | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario           | 3h                    |                                   |                                                                                                                                                                                                       |
| Tensione nominale (range)    | 250-400V              | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Tensione nominale            | 380V 50Hz / 440V 60Hz | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Frequenza d'impiego          | 60Hz                  |                                   |                                                                                                                                                                                                       |
| Frequenza d'impiego          | 50Hz                  |                                   |                                                                                                                                                                                                       |
| Colore                       | ROSSO                 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Materiale                    | TERMOPLASTICO         |                                   |                                                                                                                                                                                                       |
| Grado di protezione generico | Stagno all'immersione |                                   |                                                                                                                                                                                                       |
| Grado di protezione IP       | IP66/IP67/IP69        |                                   |                                                                                                                                                                                                       |
| Grado di protezione IK       | IK08                  |                                   |                                                                                                                                                                                                       |
| Tipo di uscite disponibili   | DIRITTA               |                                   |                                                                                                                                                                                                       |
| Morsetti                     | Morsetti a vite       |                                   |                                                                                                                                                                                                       |

|                                |               |
|--------------------------------|---------------|
| Materiale di contatto          | CuZn (ottone) |
| Trattamento superficiale cont. | Nichelato     |
| Uscita cavo                    | PRESSACAVO    |