



318.6347

PRESA MOBILE

63A 3P+N+T 6h 346-415V 50Hz 60Hz Morsetti a mantello

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie OPTIMA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	PRESA MOBILE	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA MOBILE		
Tipo installazione	PORTATILE		
Corrente nominale	63A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	6h		
Tensione nominale (range)	250-400V	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensione nominale	346-415V		
Frequenza d'impiego	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Frequenza d'impiego	50Hz		
Colore	ROSSO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Materiale	TERMOPLASTICO		
Grado di protezione generico	Stagno all'immersione		
Grado di protezione IP	IP66/IP67/IP69		
Grado di protezione IK	IK08		
Tipo di uscite disponibili	DIRITTA		
Morsetti	Morsetti a mantello		

Materiale di contatto	CuZn (ottone)
Uscita cavo	PRESSACAVO
Note	EASY-PLUG