



Remote control switch with 2 NO contacts, with series connection Contact for 230 V AC, 400V 16A Control 230 V AC

Model	
product brand name	SETRON
product designation	Remote control switch
latching relay design	Mechanical two-circuit switch
General technical data	
electrical endurance (operating cycles)	50 000
galvanic isolation between magnet coil and contact	Yes
switching voltage of the contacts at AC minimum	10 V
switching current at AC per contact minimum	100 mA
power loss [V·A] of magnet coil with pulse rated value	7 VA
Voltage	
type of voltage of the operating voltage	AC
continuous voltage fuse version	Yes
operating range factor control supply voltage rated value at AC at 50 Hz	
• initial value	0.8
• full-scale value	1.1
surge voltage resistance rated value	4 kV
supply voltage	250 V
Supply voltage	
supply voltage minimum	250 V
Protection class	
protection class IP	IP20, with connected conductors
Breaking Capacity	
switching capacity apparent power	
• for fluorescent lamp load with DUO circuit	900 VA
• for fluorescent lamp load with parallel compensation	400 VA
• for uncompensated fluorescent lamp load	500 VA
switching capacity current	
• at cos phi 0.6	16 A
• rated value	16 A
switching capacity active power with incandescent lamp load	2 000 W
Dissipation	
power loss [W]	
• at 16 A per contact rated value	1.2 W
• of magnet coil with pulse rated value	4.5 W
Control current	
type of voltage	
• of control voltage_1	AC
control voltage	

<ul style="list-style-type: none"> • _1 initial value • _1 full-scale value • _1 setpoint 	184 V 253 V 230 V
control voltage frequency	
<ul style="list-style-type: none"> • _1 initial value • _1 full-scale value 	50 Hz 50 Hz
Product details	
product component switch position indicator	Yes
number of NC contacts	0
number of NO contacts	2
number of CO contacts	0
Product function	
product function direct operation	Yes
pulse duration minimum	50 ms
Number	
number of terminals	6
Connections	
connectable conductor cross-section for flexible conductor with core end processing	
<ul style="list-style-type: none"> • minimum • maximum 	1 mm ² 6 mm ²
connectable conductor cross-section for rigid conductor	
<ul style="list-style-type: none"> • minimum • maximum 	1 mm ² 6 mm ²
tightening torque with screw-type terminals	
<ul style="list-style-type: none"> • minimum • maximum 	0.8 N·m 1 N·m
Mechanical Design	
width of opening of the contacts	1.2 mm
mounting height	90 mm
installation depth	70 mm
number of modular width units	1
fastening method	DIN rail
mounting position	any
required spacing for live parts	6 mm
net weight	143 g
Environmental conditions	
ambient temperature during operation	
<ul style="list-style-type: none"> • minimum • maximum 	-10 °C 40 °C
Approvals Certificates	
General Product Approval	



[Confirmation](#)



[Miscellaneous](#)



Test Certificates	other	Environment
Miscellaneous	Confirmation	Miscellaneous
		Environmental Confirmations

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4132-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4132-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4132-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

8/5/2021

