



Remote control switch with 1 NO contact, Contact for 230 V AC 16 A Control 12V DC

Model	
product brand name	SETRON
product designation	Remote control switch
latching relay design	Mechanical switch
General technical data	
electrical endurance (operating cycles)	50 000
galvanic isolation between magnet coil and contact	Yes
switching voltage of the contacts at AC minimum	10 V
switching current at AC per contact minimum	100 mA
power loss [V·A] of magnet coil with pulse rated value	7 VA
Voltage	
type of voltage of the operating voltage	DC
continuous voltage fuse version	Yes
operating range factor control supply voltage rated value at AC at 50 Hz	
• initial value	0.8
• full-scale value	1.1
surge voltage resistance rated value	4 kV
supply voltage	250 V
Supply voltage	
supply voltage minimum	250 V
Protection class	
protection class IP	IP20, with connected conductors
Breaking Capacity	
switching capacity apparent power	
• for fluorescent lamp load with DUO circuit	900 VA
• for fluorescent lamp load with parallel compensation	400 VA
• for uncompensated fluorescent lamp load	500 VA
switching capacity current	
• at cos phi 0.6	16 A
• rated value	16 A
switching capacity active power with incandescent lamp load	2 000 W
Dissipation	
power loss [W]	
• at 16 A per contact rated value	1.2 W
Control current	
type of voltage	
• of control voltage_1	DC
control voltage	
• _1 initial value	9.6 V

<ul style="list-style-type: none"> <li>• _1 full-scale value</li> <li>• _1 setpoint</li> </ul>	13.2 V 12 V
control voltage frequency	
<ul style="list-style-type: none"> <li>• _1 initial value</li> <li>• _1 full-scale value</li> </ul>	50 Hz 50 Hz
<b>Product details</b>	
product component switch position indicator	Yes
number of NC contacts	0
number of NO contacts	1
number of CO contacts	0
<b>Product function</b>	
product function direct operation	Yes
pulse duration minimum	50 ms
<b>Number</b>	
number of terminals	4
<b>Connections</b>	
connectable conductor cross-section for flexible conductor with core end processing	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	1 mm <sup>2</sup> 6 mm <sup>2</sup>
connectable conductor cross-section for rigid conductor	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	1 mm <sup>2</sup> 6 mm <sup>2</sup>
tightening torque with screw-type terminals	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	0.8 N·m 1 N·m
<b>Mechanical Design</b>	
width of opening of the contacts	1.2 mm
mounting height	90 mm
installation depth	70 mm
number of modular width units	1
fastening method	DIN rail
mounting position	any
required spacing for live parts	6 mm
net weight	149 g
<b>Environmental conditions</b>	
ambient temperature during operation	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	-10 °C 40 °C
<b>Approvals Certificates</b>	
<b>General Product Approval</b>	



[Confirmation](#)



[Miscellaneous](#)



Test Certificates	other	Environment
<a href="#">Miscellaneous</a>	<a href="#">Miscellaneous</a>	<a href="#">Confirmation</a>
		<a href="#">Environmental Confirmations</a>

#### Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

<http://www.siemens.com/lowvoltage/catalogs>

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4111-3>

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4111-3>

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TT4111-3](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4111-3)

<http://www.siemens.com/cax>

<http://www.siemens.com/specifications>



8/5/2021 

