

product type designation



PROFIBUS OLM/G11 V4.0

PROFIBUS OLM/G11 V4.0 optical link module with 1 RS 485 and 1 glass fiber optic cable interface (2 BFOC sockets), with signaling contact and test port

transfer rate	
transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / with PROFIBUS PA	45.45 kbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	2
number of electrical connections	
• for network components or terminal equipment	1
• for measuring device	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply and signaling contact	5-pole terminal block
number of optical interfaces / for fiber optic cable	1
design of the optical interface / for fiber optic cable	BFOC port
optical data	
attenuation factor / of the FOC transmission link	
• for glass FOC with 50/125 µm / at 3 dB/km / maximum	10 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum	12 dB
propagation delay [bit]	6.5 bit
connectable optical power relative to 1 mW	
• for glass FOC with 50/125 µm / at 3 dB/km	-16 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km	-13 dB
optical sensitivity relating to 1 mW	
• for glass FOC with 50/125 µm / at 3 dB/km	-28 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km	-28 dB
wavelength / of the optical interface / note	860 nm, multimode
wire length	
• for glass FOC with 50/125 µm / at 3 dB/km / maximum	3 km
• for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum	3 km
signal inputs/outputs	
operating voltage / of the signaling contacts / at DC / rated value	24 V
operational current / of the signaling contacts / at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC

supply voltage / at DC / rated value	24 V
supply voltage / at DC	18.8 ... 28.8 V
product component / fusing at power supply input	Yes
consumed current / at DC / at 24 V / maximum	0.2 A
ambient conditions	
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40
design, dimensions and weights	
design	compact
width	39.5 mm
height	112 mm
depth	74.5 mm
net weight	340 g
fastening method	
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	Yes
product functions / redundancy	
product function / ring redundancy	Yes
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 Nr. 60950-1
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• CE marking	Yes
• C-Tick	Yes
• CCC / for hazardous zone according to GB standard	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• French marine classification society (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
further information / internet links	
internet link	
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)
last modified:	10/12/2023 

