

product type designation



PROFIBUS OLM/G22 V4.0

PROFIBUS OLM/G22 V4.0; Optical link module with 2 RS 485 and 2 glass fiber optic cable interfaces (4 BFOC sockets) for standard Distances up to 2850 m; with signaling contact and measuring output.

| transfer rate | |
|---|--------------------------|
| transfer rate / with PROFIBUS | 9.6 kbit/s ... 12 Mbit/s |
| transfer rate / with PROFIBUS PA | 45.45 kbit/s |
| interfaces | |
| number of electrical/optical connections / for network components or terminal equipment / maximum | 4 |
| number of electrical connections | |
| • for network components or terminal equipment | 2 |
| • for measuring device | 1 |
| • for signaling contact | 1 |
| • for power supply | 1 |
| • for redundant voltage supply | 1 |
| type of electrical connection | |
| • for network components or terminal equipment | 9-pin Sub-D socket |
| • for measuring device | 2-pole terminal block |
| • for power supply and signaling contact | 5-pole terminal block |
| number of optical interfaces / for fiber optic cable | 2 |
| design of the optical interface / for fiber optic cable | BFOC port |
| optical data | |
| attenuation factor / of the FOC transmission link | |
| • for glass FOC with 50/125 µm / at 3 dB/km / maximum | 10 dB |
| • for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum | 12 dB |
| propagation delay [bit] | 6.5 bit |
| connectable optical power relative to 1 mW | |
| • for glass FOC with 50/125 µm / at 3 dB/km | -16 dB |
| • for glass FOC with 62.5/125 µm / at 3.5 dB/km | -13 dB |
| optical sensitivity relating to 1 mW | |
| • for glass FOC with 50/125 µm / at 3 dB/km | -28 dB |
| • for glass FOC with 62.5/125 µm / at 3.5 dB/km | -28 dB |
| wavelength / of the optical interface / note | 860 nm, multimode |
| wire length | |
| • for glass FOC with 50/125 µm / at 3 dB/km / maximum | 3 km |
| • for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum | 3 km |
| signal inputs/outputs | |
| operating voltage / of the signaling contacts / at DC / rated value | 24 V |
| operational current / of the signaling contacts / at DC / maximum | 0.1 A |
| supply voltage, current consumption, power loss | |
| type of voltage / of the supply voltage | DC |

| | |
|--|--|
| supply voltage / at DC / rated value | 24 V |
| supply voltage / at DC | 18.8 ... 28.8 V |
| product component / fusing at power supply input | Yes |
| consumed current / at DC / at 24 V / maximum | 0.2 A |
| ambient conditions | |
| ambient temperature | |
| • during operation | 0 ... 60 °C |
| • during storage | -40 ... +70 °C |
| • during transport | -40 ... +70 °C |
| relative humidity | |
| • at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP40 |
| design, dimensions and weights | |
| design | compact |
| width | 39.5 mm |
| height | 112 mm |
| depth | 74.5 mm |
| net weight | 340 g |
| fastening method | |
| • 35 mm top hat DIN rail mounting | Yes |
| • wall mounting | Yes |
| product functions / redundancy | |
| product function / ring redundancy | Yes |
| standards, specifications, approvals | |
| standard | |
| • for FM | FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4 |
| • for safety / from CSA and UL | UL 60950-1, CSA C22.2 Nr. 60950-1 |
| • for emitted interference | EN 61000-6-4 (Class A) |
| • for interference immunity | EN 61000-6-2 |
| certificate of suitability | EN 61000-6-2, EN 61000-6-4 |
| • CE marking | Yes |
| • C-Tick | Yes |
| • CCC / for hazardous zone according to GB standard | No |
| Marine classification association | |
| • American Bureau of Shipping Europe Ltd. (ABS) | Yes |
| • French marine classification society (BV) | Yes |
| • Det Norske Veritas (DNV) | Yes |
| • Germanische Lloyd (GL) | Yes |
| • Lloyds Register of Shipping (LRS) | Yes |
| • Nippon Kaiji Kyokai (NK) | Yes |
| further information / internet links | |
| internet link | |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAX-Download-Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| security information | |
| security information | Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4) |
| last modified: | 10/12/2023  |

