



INDUSTRIAL Campanula Industrial 21000lm

**High Bay, 150W, IK08, IP65, 21000lm, 140lm/W, 4000K,
On/Off,Black**

Model No.:

SGSO Sku:

0017160045

GTIN/EAN:

7630268415372

Mounting method:	Pendant
Lamp type:	LED not exchangeable
Housing material:	Aluminium
Housing colour:	Black
Voltage type:	AC
Nominal voltage:	100 ... 277 V
Nominal current:	490 ... 1800 mA
Type of control gear:	LED operating device current--controlled
No dim function	Yes
Light sharing:	Symmetric
Reflector:	None
Energy efficiency class of the light source according to EU regulation 2019/2015:	D
Beam angle:	Extreme wide beam >80°
Colour consistency (McAdam ellipse):	SDCM6
Rated life time L70/B50 at 25 °C:	50000 h
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	3 %
Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	22 %
Degree of protection (IP):	IP65
Impact strength:	IK08
Protection class:	I
Rated ambient temperature according to IEC 62722-2-1:	-30 ... 50 °C
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Max. system power:	150 W
Rated luminous flux according to IEC 62722-2-1:	21000 lm
Luminaire efficacy:	140 lm/W
Colour of light:	White
Colour temperature:	4000 K
Colour rendering index CRI:	80-89
Photobiological safety according to EN 62471:	RG1
Power factor:	0.9
Height/depth:	155 mm
Outer diameter:	310 mm
Type of wiring:	Ending
Conductor cross section:	1 mm ²
Connection type:	Flying cable without plug
Max. number of luminaires per miniature circuit breaker B16 (MCB):	4
Max. number of luminaires per miniature circuit breaker C16 (MCB):	8

