



JUMPER Projector LED 11000lm

Symmetric Slim Floodlight, 100W, IK07, IP65, 11000lm, 110lm/w, 3CCT 3000K-3500K-4000K, On/off, Black

Model No.:

SGSO Sku:

0017440173

GTIN/EAN:

7630268415426

Suitable for surface mounting:	Yes
Suitable for wall mounting:	Yes
Suitable for pedestal/floor mounting:	Yes
Adjustability:	Swivelling
Lamp type:	LED not exchangeable
Housing material:	Aluminium
Surface protection:	Powder coating
Housing colour:	Grey
Material cover:	Glass structured
Voltage type:	AC
Nominal voltage:	220 ... 240 V
Nominal current:	100 mA
Type of control gear:	LED operating device current--controlled
No dim function	Yes
Reflector:	Matt
Light sharing:	Symmetric
Reflector colour:	White
Beam angle:	Extreme wide beam >80°
Light outlet:	Direct
Energy efficiency class of the light source according to EU regulation 2019/2015:	E
Rated life time L70/B50 at 25 °C:	50000 h
Degree of protection (IP):	IP65
Impact strength:	IK07
Protection class:	I
Rated ambient temperature according to IEC 62722-2-1:	-20 ... 40 °C
Max. system power:	100 W
Colour of light:	White
Colour temperature:	3000K/3500K/4000K
Colour rendering index CRI:	80-89
Rated luminous flux according to IEC 62722-2-1:	11000 lm
Luminous intensity:	4208 cd
Power factor:	0.9
Flickering value Pst LM:	1
Colour of light adjustable:	Positions
Width:	222.4 mm
Height/depth:	43.8 mm
Length:	300 mm
Type of wiring:	Ending
Conductor cross section:	1 mm ²
Connectable conductor cross section:	1 mm ²
Connection type:	Other
Max. number of luminaires per miniature circuit breaker B16 (MCB):	20
Max. number of luminaires per miniature circuit breaker C16 (MCB):	30
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Luminaire efficacy:	110 lm/W
Photobiological safety according to EN 62471:	RG1
Colour consistency (McAdam ellipse):	SDCM5
Unified Glare Ratio (UGR):	31

