

**VG 9-MS54-ZE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

**General ordering data**

|            |                                                                                                                                      |
|------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Version    | VG MS ZE (standard brass cable gland strain relief), Cable glands, PG 9, 6 mm, OD min. 4 - OD max. 10 mm, IP65, Brass, nickel-plated |
| Order No.  | <a href="#">1718810000</a>                                                                                                           |
| Type       | VG 9-MS54-ZE                                                                                                                         |
| GTIN (EAN) | 4008190352035                                                                                                                        |
| Qty.       | 50 pc(s).                                                                                                                            |

## VG 9-MS54-ZE

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Length     | 30.5 mm | Length (inches) | 1.201 inch |
| Net weight | 27.1 g  |                 |            |

## Temperatures

|                       |                |
|-----------------------|----------------|
| Operating temperature | -20 °C...80 °C |
|-----------------------|----------------|

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## General information

|                                     |         |                                     |                      |
|-------------------------------------|---------|-------------------------------------|----------------------|
| AF size                             | 19 mm   | AF size 1                           | 19 mm                |
| AF size 2                           | 17 mm   | Cable glands                        | PG                   |
| Clamping range, strain relief, max. | 10 mm   | Clamping range, strain relief, min. | 6.5 mm               |
| External thread                     | PG 9    | Halogen                             | No                   |
| Length of thread                    | 6 mm    | Material                            | Brass, nickel-plated |
| Operating temperature range, max.   | 80 °C   | Operating temperature range, min.   | -20 °C               |
| Outer cable diameter, max.          | 10 mm   | Outer cable diameter, min.          | 4 mm                 |
| Protection degree                   | IP54    | Protection degree with GWDR         | IP65                 |
| Seal insert                         | NBR     | Torque for cap nut, max.            | 4.2 Nm               |
| Torque for cap nut, min.            | 4.2 Nm  | Torque for connecting adapter, max. | 6.25 Nm              |
| Torque for connecting adapter, min. | 6.25 Nm |                                     |                      |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000441    | ETIM 7.0    | EC000441    |
| ETIM 8.0    | EC000441    | ECLASS 9.0  | 27-14-44-32 |
| ECLASS 9.1  | 27-14-44-32 | ECLASS 10.0 | 27-14-44-32 |
| ECLASS 11.0 | 27-14-44-32 |             |             |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">EPLAN, WSCAD</a>             |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |