

WSMH 108MM

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Similar to illustration

WSM is a complete marking system for cables, conductors, pipes and components - it offers permanent labelling in environments which no other marker is able to withstand. This product line consists of labelling plates, carriers and stainless steel cable ties – available individually or complete in the WSM Set and Service Box.

Advantages:

- Sturdy embossed characters for maximum legibility
- Resistant to heat, cold, corrosion, acids, chemicals, fire,
- Individual and multi-character markings, can also be combined
- Quick installation
- Ideal for outdoor applications
- Easy attachment with cable ties

General ordering data

| Version | Stainless steel markers, Conductor and cable markers, 108 x 11 mm, silver |
|------------|---|
| Order No. | <u>1774530000</u> |
| Туре | WSMH 108MM |
| GTIN (EAN) | 4032248149322 |
| Qty. | 50 pc(s). |



WSMH 108MM

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

| - | | | |
|-----|---------|-----|---------|
| Dim | ensions | and | weights |
| | | | |

| Depth | 0.3 mm | Depth (inches) | 0.012 inch |
|------------|--------|-----------------|------------|
| Height | 108 mm | Height (inches) | 4.252 inch |
| Width | 11 mm | Width (inches) | 0.433 inch |
| Net weight | 3.56 g | | |

Temperatures

| Operating temperature range | 250 °C |
|-----------------------------|--------|

General data

| Colour | silver | Material | Stainless steel 1.4404 |
|-----------------------------|---------|-----------------------------------|--|
| Number of characters | | Number of markers per combination | 1 Component part = Conductor and cable |
| | 16 | | markers |
| Operating temperature range | 250 °C | Operating temperature range, max. | 250 °C |
| Type of printing | neutral | Width | 11 mm |

Conductor and cable markers

| Conductor cross-section, max. | 500 mm ² | Conductor cross-section, min. | 16 mm ² | |
|----------------------------------|--------------------------|-------------------------------|--------------------|--|
| Cross-section for connected wire | 16 - 500 mm ² | | | |

Classifications

| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC001530 | ECLASS 9.0 | 27-40-04-01 |
| ECLASS 9.1 | 27-40-04-01 | ECLASS 10.0 | 27-40-04-01 |
| ECLASS 11.0 | 27-28-11-02 | | |

Approvals

| ROHS | Conform | |
|------|---------|--|

Downloads

| Engineering Data | EPLAN, WSCAD |
|------------------|--------------------------|
| Catalogues | Catalogues in PDF-format |