

**VGM25-MS54 ZE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

**General ordering data**

Version	VG MS ZE (standard brass cable gland strain relief), Cable glands, M 25, 7 mm, OD min. 9 - OD max. 19 mm, IP65, Brass, nickel-plated
Order No.	<a href="#">1778480000</a>
Type	VGM25-MS54 ZE
GTIN (EAN)	4032248161492
Qty.	25 pc(s).

Creation date October 30, 2021 12:29:35 PM CEST

Catalogue status 22.10.2021 / We reserve the right to make technical changes.

## VGM25-MS54 ZE

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Length	38 mm	Length (inches)	1.496 inch
Net weight	93.9 g		

### Temperatures

Operating temperature	-20 °C...80 °C
-----------------------	----------------

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

### General information

AF size	30 mm	AF size 1	34 mm
AF size 2	30 mm	Cable glands	metric
Clamping range, strain relief, max.	21 mm	Clamping range, strain relief, min.	12 mm
External thread	M 25	Halogen	No
Length of thread	7 mm	Material	Brass, nickel-plated
Operating temperature range, max.	80 °C	Operating temperature range, min.	-20 °C
Outer cable diameter, max.	19 mm	Outer cable diameter, min.	9 mm
Pitch of thread	1.5 mm	Protection degree	IP54
Protection degree with GWDR	IP65	Seal insert	NBR
Torque for cap nut, max.	8 Nm	Torque for cap nut, min.	8 Nm
Torque for connecting adapter, max.	12 Nm	Torque for connecting adapter, min.	12 Nm

### Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ETIM 8.0	EC000441	ECLASS 9.0	27-14-44-32
ECLASS 9.1	27-14-44-32	ECLASS 10.0	27-14-44-32
ECLASS 11.0	27-14-44-32		

### Approvals

ROHS	Conform
------	---------

### Downloads

Engineering Data	<a href="#">EPLAN, WSCAD</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	