

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

# **General ordering data**

Version	HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Coupling housing, Side-locking clamp on lower side, Standard, Size of cable entries: M 20
Order No.	<u>1787720000</u>
Туре	HDC 10B KBU 1M20G
GTIN (EAN)	4032248205066
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

## **Dimensions and weights**

Depth	115.7 mm	Depth (inches)	4.555 inch
Height	55 mm	Height (inches)	2.165 inch
Width	55 mm	Width (inches)	2.165 inch
Net weight	211 g		

## **Temperatures**

Limit temperature -40 °C ... 125 °C

### **Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1, Potassium perfluc	probutane sulfonate 29420-49-3	
Chemical resistance	Substance	Acetone	
	Chemical resistance	Conditionally resistant	
	Substance	Drilling oil	
	Chemical resistance	Resistant	
	Substance	Diesel	
	Chemical resistance	Resistant	
	Substance	Ethyl alcohol	
	Chemical resistance	Resistant	
	Substance	Transmission oil	
	Chemical resistance	Resistant	
	Substance	Hydraulic oil	
	Chemical resistance	Resistant	
	Substance	Coolant	
	Chemical resistance	Resistant	
	Substance	Petroleum benzine	
	Chemical resistance	Resistant	
	Substance	Sweat	
	Chemical resistance	Resistant	
	Substance	Premium gasoline	
	Chemical resistance	Conditionally resistant	
	Substance	Water	
	Chemical resistance	Resistant	
	Substance	UV	
	Chemical resistance	Unstable	
	Substance	Ozone	
	Chemical resistance	Unstable	

### **Dimensions**

Cable entry	w. threading	Height of housing B	54.65 mm	
Total length housing	73 mm	Width housing C	43 mm	

### **General data**

EMC housings	No	Housing main material	diecast aluminium
Material of locking element		Protection degree	IP65 (in plugged
	Stainless steel, rust-proof		condition)
Surface finish	Powder coating		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

#### Version

Cable entry	w. threading	Clamp version	Side-locking clamp
Colour (RAL)	RAL 7035	Design	Standard
Design of housing	Coupling housing	Design of locking system	Side-locking clamp on lower side
Internal thread	M 20	Number of cable entry on top	1
Number of cable entry sideways	0	Sealing	NBR
Size	4	Size of cable entries	M 20
Suitable for ModuPlug <sup>®</sup>	No	Top part/bottom part/lid	lower part
Type	coupling extension		

### Classifications

ETIM 6.0	EC000437	ETIM 7.0	EC000437
ETIM 8.0	EC000437	ECLASS 9.0	27-44-02-02
ECLASS 9.1	27-44-02-02	ECLASS 10.0	27-44-02-02
FCLASS 11.0	27-44-02-02		

#### **Approvals**

Approvals			ji
	<b>(</b> -	. 🕶	<b>1 1</b>
	•		

ROHS	Conform	
UL File Number Search	E92202	

## **Downloads**

Approval/Certificate/Document of		
Conformity	Manufacturer's declaration	
Engineering Data	STEP	
Engineering Data	EPLAN, WSCAD	
Technical Documentation	1787720000_HDC_10B_KBU_1M20G_STP_Blatt1.pdf	
Catalogues	Catalogues in PDF-format	
Brochures	FL FIELDWIRING EN	
	<u>FL FIELDWIRING EN</u>	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Drawings**

