

**HDC 25A TSLU 1M25G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

**General ordering data**

|            |                                                                                                                                                                                |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | HDC enclosures, Size: 5, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, End-locking clamp, lower side, high, Size of cable entries: M 25 |
| Order No.  | <a href="#">1788690000</a>                                                                                                                                                     |
| Type       | HDC 25A TSLU 1M25G                                                                                                                                                             |
| GTIN (EAN) | 4032248206230                                                                                                                                                                  |
| Qty.       | 1 pc(s).                                                                                                                                                                       |

## HDC 25A TSLU 1M25G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 89 mm   | Depth (inches)  | 3.504 inch |
| Height     | 72 mm   | Height (inches) | 2.835 inch |
| Width      | 32.5 mm | Width (inches)  | 1.28 inch  |
| Net weight | 167 g   |                 |            |

## Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

## Environmental Product Compliance

| REACH SVHC          | Lead 7439-92-1      |                         |
|---------------------|---------------------|-------------------------|
| Chemical resistance | Substance           | Acetone                 |
|                     | Chemical resistance | Conditionally resistant |
|                     | Substance           | Drilling oil            |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Diesel                  |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Ethyl alcohol           |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Transmission oil        |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Hydraulic oil           |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Coolant                 |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Petroleum benzine       |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Sweat                   |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | Premium gasoline        |
|                     | Chemical resistance | Conditionally resistant |
|                     | Substance           | Water                   |
|                     | Chemical resistance | Resistant               |
|                     | Substance           | UV                      |
|                     | Chemical resistance | Unstable                |
| Substance           | Ozone               |                         |
| Chemical resistance | Unstable            |                         |

## Dimensions

|                      |              |                     |         |
|----------------------|--------------|---------------------|---------|
| Cable entry          | w. threading | Height of housing B | 72 mm   |
| Total length housing | 79 mm        | Width housing C     | 29.5 mm |

## General data

|                             |                             |                       |                             |
|-----------------------------|-----------------------------|-----------------------|-----------------------------|
| EMC housings                | No                          | Housing main material | diecast aluminium           |
| Material of locking element | Stainless steel, rust-proof | Protection degree     | IP65 (in plugged condition) |
| Surface finish              | Powder coating              | Tightening torque     | 0.5 Nm                      |

**HDC 25A TSLU 1M25G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Version**

|                                |                                     |                              |                               |
|--------------------------------|-------------------------------------|------------------------------|-------------------------------|
| Cable entry                    | w. threading                        | Clamp version                | End-locking clamp             |
| Colour (RAL)                   | RAL 7035                            | Design                       | high                          |
| Design of housing              | Cable entry from side, Plug housing | Design of locking system     | End-locking clamp, lower side |
| Internal thread                | M 25                                | Number of cable entry on top | 0                             |
| Number of cable entry sideways | 1                                   | Sealing                      | NBR                           |
| Size                           | 5                                   | Size of cable entries        | M 25                          |
| Suitable for ModuPlug®         | No                                  | Tightening torque            | 0.5 Nm                        |
| Top part/bottom part/lid       | upper part                          | Type                         | Plug                          |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ETIM 8.0    | EC000437    | ECLASS 9.0  | 27-44-02-02 |
| ECLASS 9.1  | 27-44-02-02 | ECLASS 10.0 | 27-44-02-02 |
| ECLASS 11.0 | 27-44-02-02 |             |             |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E92202  |

**Downloads**

|                         |                                                                        |
|-------------------------|------------------------------------------------------------------------|
| Engineering Data        | <a href="#">STEP</a>                                                   |
| Engineering Data        | <a href="#">EPLAN, WSCAD</a>                                           |
| Technical Documentation | <a href="#">1788690000 HDC 25A TSLU 1M25G STP Blatt 1.pdf</a>          |
| Catalogues              | <a href="#">Catalogues in PDF-format</a>                               |
| Brochures               | <a href="#">FL FIELDWIRING EN</a><br><a href="#">FL FIELDWIRING EN</a> |

### HDC 25A TSLU 1M25G

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

