

**TM 205/20 V0****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

**General ordering data**

|            |                                                                          |
|------------|--------------------------------------------------------------------------|
| Version    | TM, Socket x 14 mm, PVC, Colour: Transparent, Conductor O.D.: 10 - 14 mm |
| Order No.  | <a href="#">1806370000</a>                                               |
| Type       | TM 205/20 V0                                                             |
| GTIN (EAN) | 4032248275885                                                            |
| Qty.       | 200 pc(s).                                                               |

## TM 205/20 V0

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |       |                 |            |
|------------|-------|-----------------|------------|
| Depth      | 14 mm | Depth (inches)  | 0.551 inch |
| Height     | 20 mm | Height (inches) | 0.787 inch |
| Width      | 14 mm | Width (inches)  | 0.551 inch |
| Net weight | 1.1 g |                 |            |

## Temperatures

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -40...80 °C |
|-----------------------------|-------------|

## General data

|                                   |             |                                   |                           |
|-----------------------------------|-------------|-----------------------------------|---------------------------|
| Colour                            | Transparent | Material                          | PVC                       |
| Operating temperature range       | -40...80 °C | Operating temperature range, max. | 80 °C                     |
| Operating temperature range, min. | -40 °C      | Recommended industries            | Transportation, Machinery |
| Type of printing                  | neutral     | UL 94 flammability rating         | V-0                       |
| Width                             | 14 mm       |                                   |                           |

## Conductor and cable markers

|                               |                    |                                  |                         |
|-------------------------------|--------------------|----------------------------------|-------------------------|
| Conductor O.D.                | 10 - 14 mm         | Conductor O.D., max.             | 14 mm                   |
| Conductor O.D., min.          | 10 mm              | Conductor cross-section, max.    | 35 mm <sup>2</sup>      |
| Conductor cross-section, min. | 16 mm <sup>2</sup> | Cross-section for connected wire | 16 - 35 mm <sup>2</sup> |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ECLASS 9.0  | 27-40-04-01 |
| ECLASS 9.1  | 27-40-04-01 | ECLASS 10.0 | 27-40-04-01 |
| ECLASS 11.0 | 27-28-11-02 |             |             |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                             |                                                                                          |
|-----------------------------|------------------------------------------------------------------------------------------|
| Engineering Data            | <a href="#">STEP</a>                                                                     |
| Engineering Data            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| Product Change Notification | <a href="#">PCN Transparent Sleeves_DE</a><br><a href="#">PCN Transparent Sleeves_EN</a> |
| Catalogues                  | <a href="#">Catalogues in PDF-format</a>                                                 |