

## **SAIS-4-IDC M8 SMALL**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female sockets for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M8 round plug-in connectors are particularly suited to applications where space is limited.

The IDC is simple and quick to assemble since this technology allows the conductor to be inserted directly into the terminal point, without crimping or having to strip the insulation. It also has excellent functional security.

#### **General ordering data**

Version	Plugs prefabricated to customer spec., M8, pin, straight
Order No.	<u>1784060001</u>
Туре	SAIS-4-IDC M8 SMALL
GTIN (EAN)	4032248429912
Qty.	1 pc(s).



## **SAIS-4-IDC M8 SMALL**

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

-			
Dım	ensions	and	weights

Matsucialat	7	
Net weight	,	g

## **Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

# Technical data customisable plug-in connectors

Cable diameter	3.25.4 mm	Cable diameter, max.
Cable diameter, min.	3.2 mm	Coding
Conductor cross-section, max.	0.34 mm <sup>2</sup>	Conductor cross-section
Connection cross-section, max.	0.34 mm <sup>2</sup>	Connection cross-section
Contact surface	tinned	Housing main material
Insulation strength	10 <sup>8</sup> Ω	Number of poles
Plugging cycles	≥ 50	Pollution severity
Protection degree	IP67	Rated current
Rated voltage	32 V	Rated voltage
Shield connection	No	Temperature range of h
Threaded ring material		Type of connection
	Diecast zinc	

Cable diameter, max.	5.4 mm
Coding	none, A
Conductor cross-section, min.	0.14 mm <sup>2</sup>
Connection cross-section, min.	0.14 mm <sup>2</sup>
Housing main material	CuZn
Number of poles	4
Pollution severity	3
Rated current	4 A
Rated voltage	32 V
Temperature range of housing	-25+85 °C
Type of connection	Insulation displacement

#### **Standards**

Connector standard IEC 61076-2-104

#### Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC002635
ETIM 8.0	EC002635	ECLASS 9.0	27-44-01-02
ECLASS 9.1	27-44-01-03	ECLASS 10.0	27-44-01-02
ECLASS 11.0	27-44-01-02		

# Approvals

Approvals



ROHS Conform

#### **Downloads**

Engineering Data	STEP	
Catalogues	Catalogues in PDF-format	
Brochures	FL FIELDWIRING EN FL FIELDWIRING EN	