

**SF 5/12 MC NE WS V2****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration



SlimFix are conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. They consist of halogen-free material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

**Advantages:**

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm<sup>2</sup>
- Markers in proven MultiCard format

**General ordering data**

|                    |                                                                                  |
|--------------------|----------------------------------------------------------------------------------|
| Version            | SlimFix, Conductor and cable markers, 4.7 - 7.4 mm, 12 x 7.4 mm, white           |
| Order No.          | <a href="#">1919650000</a>                                                       |
| Type               | SF 5/12 MC NE WS V2                                                              |
| GTIN (EAN)         | 4032248556076                                                                    |
| Qty.               | 160 pc(s).                                                                       |
| compatible printer | <a href="#">2715590000</a> <a href="#">2438520000</a> <a href="#">2438510000</a> |

## SF 5/12 MC NE WS V2

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 8 mm    | Depth (inches)  | 0.315 inch |
| Height     | 12 mm   | Height (inches) | 0.472 inch |
| Width      | 7.4 mm  | Width (inches)  | 0.291 inch |
| Net weight | 0.775 g |                 |            |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...100 °C |
|-----------------------------|--------------|

## General data

|                                   |                                           |                                              |              |
|-----------------------------------|-------------------------------------------|----------------------------------------------|--------------|
| Colour                            | white                                     | Halogen                                      | No           |
| Material                          | Polyamide 66                              | Material colour according to resistance code | 9            |
| Number of markers per combination | 1 MultiCard = Conductor and cable markers | Operating temperature range                  | -40...100 °C |
| Operating temperature range, max. | 100 °C                                    | Operating temperature range, min.            | -40 °C       |
| Recommended industries            | Transportation, Machinery                 | Size of labelling field                      | 12 x 7.4 mm  |
| Type of printing                  | neutral                                   | UL 94 flammability rating                    | V-2          |
| Width                             | 7.4 mm                                    |                                              |              |

## Conductor and cable markers

|                               |                   |                                  |                        |
|-------------------------------|-------------------|----------------------------------|------------------------|
| Conductor O.D.                | 4.7 - 7.4 mm      | Conductor O.D., max.             | 7.4 mm                 |
| Conductor O.D., min.          | 4.7 mm            | Conductor cross-section, max.    | 10 mm <sup>2</sup>     |
| Conductor cross-section, min. | 6 mm <sup>2</sup> | Cross-section for connected wire | 6 - 10 mm <sup>2</sup> |
| Halogen                       | No                |                                  |                        |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ECLASS 9.0  | 27-40-04-01 |
| ECLASS 9.1  | 27-40-04-01 | ECLASS 10.0 | 27-40-04-01 |
| ECLASS 11.0 | 27-28-11-02 |             |             |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                             |                                                                                                                            |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Engineering Data            | <a href="#">STEP</a>                                                                                                       |
| Engineering Data            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                                                   |
| Product Change Notification | <a href="#">Technical change to MultiCard material - DE</a><br><a href="#">Technical change to MultiCard material - EN</a> |
| Catalogues                  | <a href="#">Catalogues in PDF-format</a>                                                                                   |

### SF 5/12 MC NE WS V2

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

