

SAISW-M8-4P(TL)

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female sockets for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M8 round plug-in connectors are particularly suited to applications where space is limited.

The solder connection provides high contact density on a small area. With this technology the stripped conductor is soldered to the contacts, producing good electrical conductivity.

General ordering data

| Version | Plugs prefabricated to customer spec., M8, pin, 90° |
|------------|---|
| Order No. | <u>1921000000</u> |
| Туре | SAISW-M8-4P(TL) |
| GTIN (EAN) | 4032248562442 |
| Qty. | 1 pc(s). |



SAISW-M8-4P(TL)

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 9 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data customisable plug-in connectors

| Cable diameter | 3.55 mm |
|--------------------------------|----------------------|
| Cable diameter, min. | 3.5 mm |
| Conductor cross-section, max. | 0.25 mm ² |
| Connection cross-section, max. | 0.25 mm ² |
| Contact surface | Gold-plated |
| Insulation strength | 10 ⁸ Ω |
| Plugging cycles | ≥ 100 |
| Protection degree | IP67 |
| Rated voltage | 60 V |
| Shield connection | No |
| Threaded ring material | Diecast zinc |

| Cable diameter, max. | 5 mm |
|--------------------------------|----------------------|
| Coding | none, A |
| Conductor cross-section, min. | 0.25 mm ² |
| Connection cross-section, min. | 0.25 mm ² |
| Housing main material | PA |
| Number of poles | 4 |
| Pollution severity | 3 |
| Rated current | 4 A |
| Rated voltage | 60 V |
| Temperature range of housing | -40 +85 ° C |
| Type of connection | Solder connection |

Standards

Connector standard IEC 61076-2-104

Classifications

| ETIM 6.0 | EC002635 |
|-------------|-------------|
| ETIM 8.0 | EC002635 |
| ECLASS 9.1 | 27-44-01-03 |
| ECLASS 11.0 | 27-44-01-02 |

| ETIM 7.0 | EC002635 |
|-------------|-------------|
| ECLASS 9.0 | 27-44-01-02 |
| ECLASS 10.0 | 27-44-01-02 |
| | |

Approvals

Approvals



| ROHS | Conform |
|-----------------------|---------|
| UL File Number Search | E307231 |

Downloads

| Engineering Data | <u>STEP</u> |
|------------------|--------------------------|
| Engineering Data | WSCAD |
| Catalogues | Catalogues in PDF-format |
| Brochures | FL FIELDWIRING EN |
| | <u>FL FIELDWIRING EN</u> |