## SAIBW-8/9-M12



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

#### **General ordering data**

Version	Plugs prefabricated to customer spec., M12
Order No.	<u>1934890000</u>
Туре	SAIBW-8/9-M12
GTIN (EAN)	4032248592623
Qty.	1 pc(s).

## SAIBW-8/9-M12

# **Technical data**



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Dimensions and weights				
29 g				
Compliance				
Lead 7439-92-1				
able plug-in connectors				
8 mm	Cable diameter, min.	6 mm		
Α	Contact surface	Gold-plated		
CuSnZn (5-pole) / gold	Housing main material	Zinc diecast, nickel-plated		
8	Plugging cycles	≥ 500		
3		IP67		
2 A	Rated voltage	60 V		
250 V (4-pole) / 60 V (5- pole) / 30 V (8-pole)	Temperature range of housing	-40 +85 ° C		
Screw connection				
M12	Connection 2	Screw		
Zinc diecast, nickel-plated	Connection thread	M12		
Gold-plated	Protection degree	IP67		
≥ 500				
IEC 61076-2-101				
EC002635	FTIM 7 0	EC002635		
_	Received and the second s	27-44-01-02		
		27-44-01-02		
27-44-01-02		27 44 01 02		
Conform				
STEP				
FL FIELDWIRING EN				
	29 g Compliance Lead 7439-92-1 table plug-in connectors 8 mm A CuSnZn (5-pole) / gold plated (8-pole) 8 3 2 A 250 V (4-pole) / 60 V (5- pole) / 30 V (8-pole) Screw connection M12 Zinc diecast, nickel-plated Gold-plated ≥ 500 IEC 61076-2-101 IEC 61076-2-101 EC002635 EC002635 EC002635 27-44-01-03 27-44-01-03 27-44-01-03 27-44-01-02	29 g Compliance Lead 7439-92-1 sable plug-in connectors A A A CuSnZn (5-pole) / gold plated (8-pole) 8 3 2 A 2 A 2 S0 V (4-pole) / 60 V (5- pole) / 30 V (8-pole) Screw connection M12 M12 Zinc diecast, nickel-plated Gold-plated ≥ 500 IEC 61076-2-101 EC002635 EC002635 EC002635 EC002635 EC002635 ECLASS 9.0 ECLASS 9.0 ECLASS 9.0 ECLASS 10.0 ECLASS 10.0		