

**WKS 2/4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image****Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

**General ordering data**

|            |                                              |
|------------|----------------------------------------------|
| Version    | Accessories, Cross-connection slider, x 29.9 |
| Order No.  | <a href="#">1936 160000</a>                  |
| Type       | WKS 2/4                                      |
| GTIN (EAN) | 4032248605880                                |
| Qty.       | 50 pc(s).                                    |

## WKS 2/4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 16.1 mm  | Depth (inches)  | 0.634 inch |
| Height     | 18.86 mm | Height (inches) | 0.743 inch |
| Width      | 29.9 mm  | Width (inches)  | 1.177 inch |
| Net weight | 3.94 g   |                 |            |

## Temperatures

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |
|----------------------------------|--------|----------------------------------|--------|

## Material data

|                           |              |        |        |
|---------------------------|--------------|--------|--------|
| Material                  | Polyamide 66 | Colour | orange |
| UL 94 flammability rating | V-2          |        |        |

## System specifications

|         |                             |
|---------|-----------------------------|
| Version | Cross-connector accessories |
|---------|-----------------------------|

## Additional technical data

|                     |                 |                |         |
|---------------------|-----------------|----------------|---------|
| Installation advice | Direct mounting | Type of fixing | Plugged |
| Type of mounting    | Clamped         |                |         |

## Dimensions

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 7.9 mm |
|-----------------|--------|

## General

|                                   |                 |                 |   |
|-----------------------------------|-----------------|-----------------|---|
| Installation advice               | Direct mounting | Number of poles | 4 |
| Operating temperature range, max. | 100 °C          |                 |   |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 |             |             |

## Approvals

Approvals



ROHS

Conform

## Technical data

### Downloads

|                                             |                                                 |
|---------------------------------------------|-------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>                 |
| Engineering Data                            | <a href="#">STEP</a>                            |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| User Documentation                          | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>        |
| Brochures                                   |                                                 |