

**VPU II 0 280V/40KA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Spare arrester Type II**

Weidmüller VPU II surge protection products protect low-voltage consumer installations and electronic devices against overvoltages that can occur as a result of atmospheric discharges (thunderstorms) or switching operations (transients). The VPU II series meets the Type II and Type III requirements acc. to IEC 61643-11:2012 and Type 2 and Type 3 requirements acc. to EN 61643-11:2012. The spare arresters are coded and can only be inserted into suitable bases.

**General ordering data**

|            |                                                                  |
|------------|------------------------------------------------------------------|
| Version    | Surge voltage arrester, Low voltage, Accessories, Spare arrester |
| Order No.  | <a href="#">1352570000</a>                                       |
| Type       | VPU II 0 280V/40KA                                               |
| GTIN (EAN) | 4050118157772                                                    |
| Qty.       | 1 pc(s).                                                         |

## VPU II 0 280V/40KA

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 64 mm   | Depth (inches)  | 2.52 inch  |
| Height     | 52 mm   | Height (inches) | 2.047 inch |
| Width      | 17.8 mm | Width (inches)  | 0.701 inch |
| Net weight | 85 g    |                 |            |

## Temperatures

|                     |                       |                       |                |
|---------------------|-----------------------|-----------------------|----------------|
| Storage temperature | -40 °C...80 °C        | Operating temperature | -40 °C...70 °C |
| Humidity            | 5 - 95% rel. humidity |                       |                |

## General data

|                           |                                                   |                   |                                        |
|---------------------------|---------------------------------------------------|-------------------|----------------------------------------|
| Colour                    | orange                                            | Design            | Installation housing; 1TE, Insta IP 20 |
| Optical function display  | green = OK; red = arrester is defective - replace | Protection degree | IP20                                   |
| UL 94 flammability rating | V-0                                               | Version           | Spare arrester                         |

## Insulation coordination acc. to EN 50178

|                    |   |                        |     |
|--------------------|---|------------------------|-----|
| Pollution severity | 2 | Surge voltage category | III |
|--------------------|---|------------------------|-----|

## Rated data IEC / EN

|                                            |                                                                         |                                              |                   |
|--------------------------------------------|-------------------------------------------------------------------------|----------------------------------------------|-------------------|
| Combined pulse $U_{OC}$                    | 10 kV                                                                   | Discharge current $I_{max}$ (8/20µs) wire-PE | 40 kA             |
| Discharge current $I_n$ (8/20µs) wire-PE   | 20 kA                                                                   | Energy coordination ( $\leq 10$ m)           | Type II, Type III |
| Frequency range, max.                      | 60 Hz                                                                   | Frequency range, min.                        | 50 Hz             |
| Fuse                                       | 125 A gL > (if back up fuse > 125 A), No Fuse necessary $\leq 125$ A gG | Leakage current at $U_n$                     | 30 µA             |
| Max. continuous voltage, $U_c$ (AC)        | 280 V                                                                   | Number of poles                              | 1                 |
| Protection level $U_p$ at $I_n$ (L/N-PE)   | $\leq 1.55$ kV                                                          | Rated voltage (AC)                           | 230 V             |
| Requirements category acc. to IEC 61643-11 | Type II, Type III                                                       | Requirements class, acc. to EN 61643-11      | T2, T3            |
| Response time                              | $\leq 25$ ns                                                            | Short-circuit current rating $I_{SCCR}$      | 25 kA             |
| Standards                                  | IEC61643-11, EN61643-11                                                 | Temporary surge voltage (over-voltage) - TOV | 438 V             |
| Voltage type                               | AC                                                                      |                                              |                   |

## Connection data

|                    |           |
|--------------------|-----------|
| Type of connection | pluggable |
|--------------------|-----------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000941    | ETIM 7.0    | EC000941    |
| ETIM 8.0    | EC000941    | ECLASS 9.0  | 27-13-08-05 |
| ECLASS 9.1  | 27-13-08-05 | ECLASS 10.0 | 27-13-08-05 |
| ECLASS 11.0 | 27-13-08-05 |             |             |

## VPU II 0 280V/40KA

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Tender specification sheets

## Long specification

Spare arrester consisting of V0 material for surge voltage arrester VPU II 280 V series The pluggable high-performance varistors can be exchanged by trained personnel following a failure. Rated voltage: 280 V Type: Weidmüller VPU II 0 280 V/40 kA Order No.: 13525750000

## Short specification

Spare arrester for surge voltage arrester VPU II 280 V series The pluggable high-performance varistors can be swapped by trained personnel following a failure. Rated voltage: 280 V Type: Weidmüller VPU II 0 280 V/40 kA Order no.: 13525750000

## Approvals

## Approvals



ROHS

Conform

## Downloads

|                                             |                                                                                                           |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC VPU SERIES</a><br><a href="#">EU_Konformitätserklärung / EU_Declaration_of_Conformity</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                                                              |
| User Documentation                          | <a href="#">Beipackzettel / Instruction sheet</a>                                                         |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                  |

## VPU II 0 280V/40KA

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Electric symbol

