

IE-SR-4TX-LTE/4G-EU**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Weidmüller Industrial Security Routers**

- Easy integration of subnets with identical IP address ranges through 1: 1 NAT
- Secure and easy remote maintenance with Weidmüller u-link remote access service
- Future-proof network connection with static and dynamic routing
- Increased network security through stateful inspection firewall, IP/Port- forwarding and network segmentation
- Secure communication over the Internet by using IPsec and OpenVPN
- Reliable internet connection, even without on-site internet access, thanks to integrated 4G/LTE cellular modem
- Full flexibility thanks to Fast Ethernet and Gigabit Ethernet interfaces ranging from 2 up to 6 ports.

General ordering data

Version	Security/NAT/VPN/U-link Router, with integrated multi-band modem (4G/3G/2G), EU-model, Fast Ethernet, 4x RJ45 10/100BaseT(X), IP30, -30 °C...70 °C
Order No.	2751280000
Type	IE-SR-4TX-LTE/4G-EU
GTIN (EAN)	4050118899962
Qty.	1 pc(s).

IE-SR-4TX-LTE/4G-EU

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	94.8 mm	Depth (inches)	3.732 inch
Height	134.5 mm	Height (inches)	5.295 inch
Width	29.9 mm	Width (inches)	1.177 inch
Net weight	213 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-30 °C...70 °C
Humidity	5 - 90 %, no condensation		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Mobile radio interface

Frequency band	EMEA, LTE: B1 (2100), B3 (1800), B7 (2600), B8 (900), B20 (800DD), UMTS/WCDMA: B1 (2100), B8 (900), GSM/GPRS/EDGE: B3 (1800), B8 (900)		
Mode of operation	Permanent connection, Manual connection control via web interface		
Transmission rate mobile radio	LTE category	CAT 4	
	Download rate, max.	150 Mbps	
	Upload rate, max.	50 Mbps	
Transmit power	LTE: +23 dBm +2.7/-2.7 dB (Power Class 3), WCDMA : 24 +1/-3 dBm (Power Class 3), GSM900: 33 ± 2 dBm (Power Class 4), GSM1800: 30 ± 2 dBm (Power Class 1)		
Wireless module	multi-band modem (4G/3G/2G)		

VPN

IPsec	OpenVPN	Configurable as OpenVPN server or client (Layer 2 and Layer 3), Authentication via X.509 certificate, Tunnel support via HTTP proxy, Maximum 10 different client or server configurations
	Configurable as IPsec server or client	
u-link	OpenVPN-based remote access service via the Weidmüller u-link cloud	

Modes of operation

IP router	IP routing (IPv4, Layer-3) with SPI firewall (Stateful Packet Inspection), Static or dynamic routing, Supports RIPv2 / OSPF	Transparent bridge
		4-port switch with additional Layer-2 filter

EMC conformity and approvals

EMC standards	EN 55032, EN 55024, EN 61000-6-2, EN 61000-6-4	Safety standard	SELV according to EN 62368-1, EN 62311
Shock	according to IEC 60068-2-27	Vibration	according to IEC 60068-2-6
Wireless	EN 301 489-1, EN 301 489-52, EN 301 511, EN 301 908-1, EN 301 908-2		

Creation date October 30, 2021 12:29:14 PM CEST

Catalogue status 22.10.2021 / We reserve the right to make technical changes.

IE-SR-4TX-LTE/4G-EU

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Environmental conditions

Humidity	5 - 90 %, no condensation	Operating temperature, max.	70 °C
Operating temperature, min.	-30 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C		

Guarantee

Time interval	3 years
---------------	---------

Interfaces

Connector for external antennas		Digital inputs	1x, galvanically isolated, VPN-initiate: establishes a pre-configured VPN connection (24 V in), Cut: physically disconnects (Link Down) the WAN port (24 V in), Trigger pre-configured packet filter rules (24 V in)
	1x SMA female		
Function reset button		LED indicator	Power: indicates power supply status, boot-up process, firmware update process, Status: indicates system status, VPN: indicates VPN tunnel status, LTE/4G: indicates mobile radio connection status, Port LED: Link/ACT, Speed (RJ45 port)
	Restoration of factory settings		
Number of SCM-Card slots	1	Number of SIM-Card slots	1
Number of ports		RJ45 ports	10/100BaseT(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
	4x RJ45 10/100BaseT(X)		
SCM-Card slot type	Smart Card (ID-000 format), Save and restore the configuration using smart card (memory chip)	SIM-Card slot type	Mini-SIM (ID-000 format)
Serial port	1x RS-485, 2-wire, galvanically isolated, 1 removable 3-pole terminal block		

Management features

Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Windows tool	Monitoring function	SNMP v1/v2c/v3, Syslog
IP-address management		Security functions	IPv4 Stateful Packet Inspection Firewall (incoming/outgoing), NAT masquerading, 1:1 NAT, IP forwarding, Port forwarding
	Static, DHCP-Client, DHCP-Server (pool-based), DHCP-Relay		
Time synchronization management	NTP client	Industrial protocol support	Modbus/TCP slave

Power supply

Connection type	1 removable 4-pin terminal block
-----------------	----------------------------------

Creation date October 30, 2021 12:29:14 PM CEST

Catalogue status 22.10.2021 / We reserve the right to make technical changes.

IE-SR-4TX-LTE/4G-EU

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Current consumption	Voltage	24 V
	Current	0.8 A
Reverse polarity protection	Yes	
Voltage supply	24 V DC, 1 single input	
Voltage supply range	Voltage type	DC
	Voltage, min.	19.2 V
	Voltage, max.	28.8 V

Technical data

Housing main material	Plastic	Protection degree	IP30
Speed	Fast Ethernet	Type of mounting	DIN rail

Classifications

ETIM 6.0	EC001478	ETIM 7.0	EC001478
ETIM 8.0	EC001478	ECLASS 9.0	19-17-01-03
ECLASS 9.1	19-17-01-03	ECLASS 10.0	19-17-04-05
ECLASS 11.0	19-17-04-05		

Approvals

Approvals



ROHS	Conform
UL File Number Search	E141197

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity RCM Declaration of Conformity Manufacturer's declaration for operating altitude
Engineering Data	STEP
Product Change Notification	Firmware Release Notes
Software	SNMP MIB file
	u-link VPN-Client - Version 2.0.194
	Router Search Utility
	Firmware
User Documentation	u-link Technical User Guide
	User Note - Secure Router Configuration
	Hardware Installation Guide
	Manual
Catalogues	Catalogues in PDF-format